

PICCOLO PC B 65 G



Sample photo

Order symbol: PC B 65 G
Product nbr: 8724303
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074001955
EI. number:
 Finland: 3423401
 Electric No. Denmark: 8212001475
 Electric No. Italy: 7201010
 Electric No. Sweden: 2536801

Including: Base with screws for mounting plate, cover with PUR gasket and polyamide cover screws.

| Dimensions: | Length | Width | Height | Accessories: | |
|-------------|--------|-------|--------|--------------|----------------------------|
| mm: | 110 | 80 | 65 | B-3 | DIN-35 Mounting rail |
| inch: | 4.3 | 3.1 | 2.6 | FP 22040 | Wall fastening lug (2 pcs) |

| Materials: | | Rating: | |
|-------------------------------|----------------------|--|--|
| Material: | Polycarbonate | Ingress Protection (EN 60529): IP66/IP67 | |
| Base colour: | RAL 7035 -light grey | Impact Resistance (EN 62262): IK08 | |
| Cover screws material: | Polyamide | Electrical insulation: Totally insulated | |
| Cover colour: | RAL 7035 -light grey | Halogen free (DIN/VDE 0472, Part 815): 1 | |
| Cover screws colour: | Grey | UV resistance: UL 508 | |
| Gasket material: | Polyurethane | Flammability Rating: UL 746C 5" | |
| | | Glow Wire Test (IEC 695-2-1) °C: 960 | |
| | | NEMA Class: NEMA 1, 4X, 6, 12, 13 | |

| Temperatures: | | Certificates: | |
|-------------------------------------|----------------|---------------|--|
| Temperature °C (short term): | -40 ... 120 °C | SGS Fimko | |
| Temperature °C (continuous): | -40 ... 80 °C | Gost R | |
| Temperature °F (short term): | -40 ... 250 °F | | |
| Temperature °F (continuous): | -40 ... 175 °F | | |

| Accessories: | |
|--------------|----------------|
| B-MP | Mounting plate |

