

# Product datasheet

Specifications



## Spacial S3D plain door w/o mount.plate. H800xW800xD250.IP66 IK10 RAL7035.

Local distributor code: 392866716 NSYS3D8825

### Main

|                             |   |
|-----------------------------|---|
| Range                       | Spacial   |
| Product name                | Spacial S3D                                       |
| Application                 | Multi-purpose                                     |
| Category                    | Compact enclosure                                 |
| Enclosure nominal height    | 800 mm  |
| Enclosure nominal width     | 800 mm  |
| Enclosure nominal depth     | 250 mm  |
| Door type                   | Plain   |
| Mounting plate description  | Without mounting plate                            |
| Type of gland plate         | Standard  |
| Installation accessory type | Wall-mounting                                     |
| Device composition          | 1 body<br>2 cable gland plate<br>1 door<br>1 lock |

### Complementary

|                             |  |
|-----------------------------|--|
| Body type                   | Single piece body<br>Gutter-shaped front rail double sheet thickness |
| Number of doors             | Front face: 1 door(s)  |
| Door opening side           | Reversible (120 °)   |
| Lock type                   | 3 points lock, 3 mm double-bar                                       |
| Accessibility for operation | Front  |
| Removable parts             | Door by hinges<br>Cable gland plate by screws                        |
| Material                    | Steel  |
| Surface finish              | Epoxy-polyester powder   |
| Colour                      | Grey (RAL 7035)  |
| Standards                   | IEC 62208  |
| Product certifications      | BV<br>cUL<br>LR<br>GL<br>UL<br>DNV                                   |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|            |       |
|------------|-------|
| Net weight | 30 kg |
|------------|-------|

## Environment

|                           |                              |
|---------------------------|------------------------------|
| NEMA degree of protection | NEMA 4X/13                   |
| IK degree of protection   | IK10 conforming to IEC 62262 |
| IP degree of protection   | IP66 conforming to IEC 60529 |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Weight             | 30.0 kg |
| Package 1 Height             | 82.4 cm |
| Package 1 width              | 82.6 cm |
| Package 1 Length             | 30.4 cm |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                     |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|