



Sample photo

**Order symbol:** PC 95/35 LG  
**Product nbr:** 6012331  
**Description:** Enclosure, PC  
**Remarks:** Grey cover

**EAN:** 6418074054616  
**El. number:**  
 Finland 3421360  
 Denmark 8212027682

**Including:** Base with PUR gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:		L	W	H	Rating:
mm:		100	100	35	<b>Ingress Protection (EN 60529):</b> IP 66/67
inch:		3.9	3.9	1.4	<b>Impact Resistance (EN 50102):</b> IK 08
<b>Materials:</b>					<b>Electrical insulation:</b> Totally insulated
<b>Material:</b>		PC			<b>Halogen free (DIN/VDE 0472, Part 815):</b> Yes
<b>Base colour:</b>		RAL 7035			<b>UV resistance:</b> UL 508
<b>Cover colour:</b>		RAL 7035			<b>Flammability Rating (UL 746 C 5):</b> UL 94 5V
<b>Cover screws material:</b>		Polyamide			<b>Glow Wire Test (IEC 695-2-1) °C:</b> 960
<b>Cover screws colour:</b>		Grey			<b>NEMA Class:</b> NEMA 1, 4, 4X, 6, 12, 13
<b>Gasket material:</b>		Polyurethane			<b>Certificates:</b>
<b>Temperatures:</b>					<b>Germanischer Lloyd (GL)</b>
<b>Short term:</b>		-40 ... 120 °C			<b>Underwriters Laboratories</b>
<b>Continuous:</b>		-40 ... 80 °C			<b>Det Norske Veritas</b>
<b>Short term:</b>		-40 ... 250 °F			<b>Fimko</b>
<b>Continuous:</b>		-40 ... 175 °F			<b>Europe EN 50298 1998</b>
<b>Accessories:</b>					<b>UL Canada</b>
MIV 95		Mounting plate			<b>Gost R</b>
B-3		DIN-35 Mounting rail			

