



Linergy - additional Neutral bar for screw distrib block - 100 A - 7 connections

LGYN1007

Range	Linergy
Product name	Linergy DS
Product or component type	Extension module
Comb busbar, distribution terminal block accessory type	Neutral bar
Poles description	1N
Accessory / separate part category	Connection accessories

Complementary

Complementary	
Distribution block outgoers	7 holes
Mounting support	Direct mounting on rear
Mounting mode	By screws
[Ue] rated operational voltage	230 V AC Ph/N
[le] rated operational current	100 A at 40 °C
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 61439-1
[lcw] rated short-time withstand current	3.5 kA for 1 s
[lpk] rated peak withstand current	20 kA
Busbar length	70 mm
9 mm pitches	7
18 mm pitches	3.5
Height	20 mm
Width	70 mm
Depth	35 mm
Net weight	63 g
Connections - terminals	Supply: screw terminal 2 cable(s) 2.525 mm² rigid

Supply: screw terminal 2 cable(s) 1.5...16 mm² flexible with cable end

Distribution: screw terminal 5 cable(s) 1.5...16 mm² rigid
Distribution: screw terminal 5 cable(s) 1.5...10 mm² flexible with cable end

Tightening torque	Supply: 2 N.m PZ2 screwdriver 7.5 mm Supply: 2 N.m flat screwdriver 7.5 mm Distribution: 2 N.m PZ2 screwdriver 5.5 mm Distribution: 2 N.m flat screwdriver 5.5 mm
Range compatibility	ComPact
Environment	
Standards	EN/IEC 61439-1 IEC 61439-2 IEC 60947-7-1
Pollution degree	3
Overvoltage category	III
Dielectric strength	2500 V
Ambient air temperature for operation	-2555 °C
Colour	White (RAL 9003)
Packing Units	
Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	8 cm
Package 1 Length	11 cm
Package 1 Weight	69 g
Unit Type of Package 2	Doboz
Number of Units in Package 2	100
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	7.48 kg
Offer Sustainability	
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months

Recommended replacement(s)

Mar 13, 2023