

PowerPacT 4

PTCCB_ODA_PHOTO_Integration

Local distributor code: 399376940 MGP1003XE2

Discontinued on: 03 November 2022

EAN Code: 3606486440827

Range of product

nange of product	, one,, det i
Product or component type	Circuit breaker
Device application	Distribution
Poles description	3P
[In] rated current	100 A at 40 °C
[Ue] rated operational voltage	415 V AC 50/60 Hz
Suitability for isolation	Yes conforming to BS EN 60947-2
Utilisation category	Category A
[lcu] rated ultimate short-circuit breaking capacity	36 kA lcu at 415 V AC 50/60 Hz
Trip unit name	MicroLogic 2.2
Trip unit technology	Electronic
Trip unit protection functions	LSol
Trip unit protection functions	200.
Control type	Toggle
Control type	Toggle
Control type Circuit breaker mounting mode	Toggle
Control type Circuit breaker mounting mode Complementary	Toggle Panel-mounted
Control type Circuit breaker mounting mode Complementary [Ui] rated insulation voltage [Uimp] rated impulse withstand	Toggle Panel-mounted 800 V
Control type Circuit breaker mounting mode Complementary [Ui] rated insulation voltage [Uimp] rated impulse withstand voltage [Ics] rated service short-circuit	Toggle Panel-mounted 800 V 8 kV
Control type Circuit breaker mounting mode Complementary [Ui] rated insulation voltage [Uimp] rated impulse withstand voltage [Ics] rated service short-circuit breaking capacity	Toggle Panel-mounted 800 V 8 kV 36 kA at 415 V AC 50/60 Hz
Control type Circuit breaker mounting mode Complementary [Ui] rated insulation voltage [Uimp] rated impulse withstand voltage [Ics] rated service short-circuit breaking capacity Mechanical durability	Toggle Panel-mounted 800 V 8 kV 36 kA at 415 V AC 50/60 Hz 50000 cycles 50000 cycles at 440 V In/2

Number of modules

Trip unit rating

3 module(s)35 mm

100 A at 40 °C

Long-time pick-up adjustment type Ir (thermal protection)	Adjustable
[Ir] long-time protection pick-up adjustment range	40100 A
Long-time protection delay adjustment type tr	Fixed
Short-time protection pick-up adjustment type Isd	Adjustable
[Isd] Short-time protection pick- up adjustment range	1.510 x lr
Short-time protection delay adjustment type tsd	Fixed
Instantaneous protection pick- up adjustment type li	Fixed
[li] instantaneous protection pick-up adjustment range	1500 A
Earth-leakage protection	Without
Zone selective interlocking ZSI	Without
Product destination	250 A panelboard 400/630 A panelboard

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty 18 months

Recommended replacement(s)

MGP1003XE2 is replaced by:



1x

Molded case circuit breaker, PowerPacT 4, 3P, Icu 36kA, MicroLogic 2.2 electronic trip unit, 100A rating

PP41003X36ML2