

Surface mounting enclosure, Insulated material, With high-grade steel screws, Number of locations 4, 3 x 30.5, 1 x 22.5



Part no. **M30-FI4-PV**

197239

EL Number

4300434

(Norway)

General specifications		
Product name		Eaton Moeller® series M30 Accessory Surface mounting enclosure
Part no.		M30-FI4-PV
EAN		4015080893103
Product Length/Depth		279 millimetre
Product height		44 millimetre
Product width		43 millimetre
Product weight		0.201 kilogram
Certifications		UL Category Control No.: NKCR CSA-C22.2 No. 94-91 CSA certified CSA file No. 012528 CE marking CSA Class No.: 3211-03 UL Listed IEC/EN 60947-5 UL 508 UL File No.: E29184 CSA-C22.2 No. 14-05
Product Tradename		M30
Product Type		Accessory
Product Sub Type		Surface mounting enclosure
Features & Functions		
Enclosure color		Gray
Enclosure material		Plastic
Fitted with:		High-grade steel screws
Knockouts		1 x M20 (cable entry knockouts at the rear) 2 x M20 (cable entry knockout at the side, 1 x each side)
Number of locations		4
RAL-number		7035
General information		
Degree of protection		NEMA 4X IP67/IP69K
Opening diameter		30 mm
Communication		
Connection to SmartWire-DT		No
Contacts		
Force for positive opening - min		0 N

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Enclosure for control circuit devices (EC000200)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecl@ss13-27-37-12-05 [AKF023019])		
Number of command positions		4
Construction type housing		Surface mounted housing
Housing material		Plastic
Housing material quality		Other
Diameter openings	mm	30
Colour housing cover		Grey
Degree of protection (IP)		IP67/IP69K
Degree of protection (NEMA)		4X
Width	mm	43

Height	mm	44
Depth	mm	279