# **Product datasheet**

Specification





# TeSys VARIO - auxiliary contact block - 1 NC early-break+1 NO late-make

Local distributor code: 20330116 VZ7

EAN Code: 3389110551969

### Main

Range	TeSys VZ	
Device Short Name		
Product Or Component Type	Auxiliary contact block	
Performance Level	High performance	
Contacts Type And Composition	on 1 NO + 1 NC	
Contact Operation	Late-make 1 NO	
	Early-break 1 NC	
Product Compatibility	V2	
	V5	
	V02	
	V6	
	V1	
	V4	
	V01	
	V0	
	V3	
Network Type	AC	
	DC	
Network Frequency	50/60 Hz	

## Complementary

Mounting Location	Left Right	
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz	
[Uimp] Rated Impulse Withstand Voltage	8 kV	
[Ith] Conventional Free Air Thermal Current	12 A	
[Ithe] Conventional Enclosed Thermal Current	10 A	
Mechanical Durability	100000 cycles	
Electrical Durability	30000 cycles DC-11 100000 cycles AC-15	
Connections - Terminals	Screw clamp terminals 2 cable(s) 0.751.5 mm² - flexible - with cable end Screw clamp terminals 2 cable(s) 12.5 mm² - solid	
Tightening Torque	0.7 N.m - on screw clamp terminals	
Height	65 mm	
Width	20 mm	
Depth	48.5 mm	
Net Weight	0.05 kg	

## **Environment**

Standards	IEC 60947-5	
Product Certifications		
Product Certifications	GL CSA	
	UL	
	UKCA	
Protective Treatment	TC	
Ip Degree Of Protection	IP20 conforming to IEC 60529	
Ambient Air Temperature For Operation	-2050 °C	
Fire Resistance	960 °C conforming to IEC 60695-2-1	

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	3.7 cm
Package 1 Length	9.0 cm
Package 1 Weight	52.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	69
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.931 kg

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>②</b>	Mercury Free	
<b>②</b>	Rohs Exemption Information	Yes
<b>②</b>	Pvc Free	
<b>⊘</b>	Halogen Free Product	

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations