

Product Technical Data Sheet - Insulation Tape

A high quality flame retardant PVC insulation tape to BS EN 60454-1, BS EN 60454-2 and BS EN 60454-3.1

It is extremely flexible and offers good adhesion.

Available in Black, Red, Yellow, Blue, Green, White, Grey, Brown and Earth(Green/Yellow)



Dimensions

Width: 19mm
 Length: ITR1 20 metres, ITR2 33 metres
 Tolerance: Thickness +/-0.01mm, width +/-0.5mm
 Cardboard core: 32mm diameter
 Packaging: Pack of 10 rolls

Properties

Total Thickness:	0.13mm	<u>Test Method</u>
Elongation:	≥160%	GB7125-1999
Peel Adhesion:	≥1.5N/cm	GB7753-1987
Tensile Strength:	≥ 20N/cm	GB2792-1998
Flammability:	≤10 seconds	GB7753-1987
Voltage Breakdown:	7Kv	UL510
Application Temp:	≤80°C	GBT4850-2002
		GBT7752-1987

For best performance this product should be stored at under 21°C and 50% relative humidity and be used within 24 months of manufacture.
 The surface this tape is to be applied to should be clean, dry and free from dust or oil.

Fully compliant to current **REACH** and **RoHS** regulations.

Partex Marking Systems (UK) LTD

61-64 Station Road, Coleshill, Birmingham B46 1JT

Tel: 01675 463670 Fax: 01675 463520 Email: sales@partex.co.uk