Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

External handle with 1242E barrel & key



Local distributor code:
392870155

NSYTHL1242EPLM

EAN Code: 3606480192784

Main

Range	Thalassa
accessory / separate part category	Locking accessory
product or component type	Handle
Application	Multi-purpose
mounting support	Direct mounting on door
Product compatibility	PLM with Height ? 847mm
Range compatibility	Thalassa Thalassa PLM
Device composition	1 cylindrical barrel 2 key 1 handle with key lock

Complementary

•	
Quantity per set	Set of 1
Lock type	Key lock
Type of keylock	Cylindrical
Kev number	1242 F

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.000 cm
Package 1 Width	5.000 cm
Package 1 Length	3.000 cm
Package 1 Weight	61.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	300
Package 2 Height	38.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	18.196 kg
Unit Type of Package 3	PAM
Number of Units in Package 3	6000

Package 3 Height	150.000 cm
Package 3 Width	100.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	385.920 kg

Logistical informations

Country of origin DE

Contractual warranty

Warranty 18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Image of product in real life situation

