



Sample photo

Order symbol: PCT 121210
Product nbr: 7022681
Description: Enclosure, PC
Remarks: Transparent cover

EAN: 6418074003775
El. number:
 Finland 3423534
 Denmark 8212002775
 Italy 7302035

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and stainless steel cover screws.

Dimensions:	L	W	H
mm:	120	122	95
inch:	4.7	4.8	3.7

Materials:	
Material:	PC
Base colour:	RAL 7035
Cover colour:	Clear transparent
Cover screws material:	Stainless steel
Gasket material:	Polyurethane

Temperatures:	
Short term:	-40 ... 120 °C
Continuous:	-40 ... 80 °C
Short term:	-40 ... 250 °F
Continuous:	-40 ... 175 °F

Accessories:	
TM 1212	Mounting plate
TRM 0812	DIN-15 Mounting rail
TRM 1212	DIN-15 Mounting rail
TRH 1212	DIN-35 Mounting rail

Rating:
Ingress Protection (EN 60529): IP 66/67
Impact Resistance (EN 50102): IK 08/07
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): Yes
UV resistance: UL 508
Flammability Rating (UL 746 C 5): UL 94 V5
Glow Wire Test (IEC 695-2-1) °C: 960
NEMA Class: NEMA 1, 4, 4X, 12, 13

Certificates:
Underwriters Laboratories
Fimko
Europe EN 50298 1998
UL Canada
Gost R

