FIBOX MNX PC 100/125 HG

Sample photo

Order symbol: PC 100/125 HG
Product nbr: 6011304

Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074022066
El. number:

Finland	3420315
Denmark	8212022056
Italy	7351035
Sweden	2535518

Including: Base with TPE gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:	L	W	H
mm:	130	80	125
inch:	5.1	3.1	4.9

Materials:

Material: PC
Base colour: RAL 7035
Cover colour: RAL 7035
Cover screws material: Polyamide
Cover screws colour: Grey
Gasket material: TPE

Temperatures:

Short term: -40 … 120 °C
Continuous: -40 … 80 °C
Short term: -40 … 250 °F
Continuous: -40 … 175 °F

Accessories:

MIV 100	Mounting plate
MIN 5	DIN-15 Mounting rail
MIN 10	DIN-15 Mounting rail
MIV 5	DIN-35 Mounting rail
MIV 10	DIN-35 Mounting rail
FP A 100/130	Front plate
HFP 130	Front plate hinge series

Rating:

Ingress Protection (EN 60529): IP 66/67
Impact Resistance (EN 50102): IK 08
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): Yes
UV resistance: UL 508
Flammability Rating (UL 746 C 5): UL 94 5V
Glow Wire Test (IEC 695-2-1) °C: 960
NEMA Class: NEMA 1, 4, 4X, 6

Certificates:

Germanischer Lloyd (GL)
Underwriters Laboratories
Det Norske Veritas
Fimko
Europe EN 50298 1998
UL Canada
Gost R



(c) Fibox OY, Data subject to change without notice