



Sample photo

Order symbol: PC 150/100 LG
Product nbr: 6012316
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074022165
EI. number:
 Finland 3420349
 Denmark 8212022153
 Italy 7351085
 Sweden 2535548

Including: Base with TPE gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:		L	W	H	Rating:
mm:		180	130	100	Ingress Protection (EN 60529): IP 66/67
inch:		7.1	5.1	3.9	Impact Resistance (EN 50102): IK 08
Materials:					
Material:		PC			
Base colour:		RAL 7035			
Cover colour:		RAL 7035			
Cover screws material:		Polyamide			
Cover screws colour:		Grey			
Gasket material:		TPE			
Temperatures:					
Short term:		-40 ... 120 °C			
Continuous:		-40 ... 80 °C			
Short term:		-40 ... 250 °F			
Continuous:		-40 ... 175 °F			
Accessories:					
MIV 150		Mounting plate			
MIN 10		DIN-15 Mounting rail			
MIN 15		DIN-15 Mounting rail			
MIV 10		DIN-35 Mounting rail			
MIV 15		DIN-35 Mounting rail			
FP A 150/180		Front plate			
HFP 180		Front plate hinge series			
Electrical insulation:		Totally insulated			
Halogen free (DIN/VDE 0472, Part 815):		Yes			
UV resistance:		UL 508			
Flammability Rating (UL 746 C 5):		UL 94 5V			
Glow Wire Test (IEC 695-2-1) °C:		960			
NEMA Class:		NEMA 1, 4, 4X, 6			
Certificates:					
		Germanischer Lloyd (GL)			
		Underwriters Laboratories			
		Det Norske Veritas			
		Fimko			
		Europe EN 50298 1998			
		UL Canada			
		Gost R			

