



Sample photo

Order symbol: PC 150/100 LT
Product nbr: 6012916
Description: Enclosure, PC
Remarks: Smoked transparent cover

EAN: 6418074022400
EI. number:
 Finland 3420457
 Denmark 8212022454
 Italy 7352085
 Sweden 2535648

Including: Base with TPE gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:			L		W		H		Rating:		
mm:	180	130	100						Ingress Protection (EN 60529): IP 66/67		
inch:	7.1	5.1	3.9						Impact Resistance (EN 50102): IK 08		
Materials:											
Material:	PC		Electrical insulation: Totally insulated								
Base colour:	RAL 7035		Halogen free (DIN/VDE 0472, Part 815): Yes								
Cover colour:	Smoked grey		UV resistance: UL 508								
Cover screws material:	Polyamide		Flammability Rating (UL 746 C 5): UL 94 5V								
Cover screws colour:	Black		Glow Wire Test (IEC 695-2-1) °C: 960								
Gasket material:	TPE		NEMA Class: NEMA 1, 4, 4X, 6								
Temperatures:											
Short term:	-40 ... 120 °C		Certificates:								
Continuous:	-40 ... 80 °C		Germanischer Lloyd (GL)								
Short term:	-40 ... 250 °F		Underwriters Laboratories								
Continuous:	-40 ... 175 °F		Det Norske Veritas								
Accessories:											
MIV 150	Mounting plate		Fimko								
MIN 10	DIN-15 Mounting rail		Europe EN 50298 1998								
MIN 15	DIN-15 Mounting rail		UL Canada								
MIV 10	DIN-35 Mounting rail		Gost R								
MIV 15	DIN-35 Mounting rail										
FP A 150/180	Front plate										
HFP 180	Front plate hinge series										

