



Sample photo

Order symbol: PC 1919 18 G
Product nbr: 5330369
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074005427
El. number:
 Finland 3423703
 Italy 7401015D
 Sweden 2539408

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

Dimensions:			L	W	H	Rating:	
mm:	188	188	180			Ingress Protection (EN 60529): IP 66/67	
inch:	7.4	7.4	7.1			Impact Resistance (EN 50102): IK 08/09	
Materials:						Electrical insulation: Totally insulated	
Material:	PC					Halogen free (DIN/VDE 0472, Part 815): Yes	
Base colour:	RAL 7035					UV resistance: UL 508	
Cover colour:	RAL 7035					Flammability Rating (UL 746 C 5): UL 94 5V	
Cover screws material:	Polyamide					Glow Wire Test (IEC 695-2-1) °C: 960	
Cover screws colour:	Grey					NEMA Class: NEMA 1, 3, 3S, 4, 4X, 6, 6P, 12	
Gasket material:	Polyurethane					Certificates:	
Temperatures:						Underwriters Laboratories	
Short term:	-40 ... 120 °C					Canadian Standards Association	
Continuous:	-40 ... 80 °C					Fimko	
Short term:	-40 ... 250 °F					Europe EN 50298 1998	
Continuous:	-40 ... 175 °F						
Accessories:							
EKHVT	Mounting plate						
EKV 12	DIN-35 Mounting rail						

