



Sample photo

Order symbol: PC 200/125 XHT
Product nbr: 6013927
Description: Enclosure, PC
Remarks: Smoked transparent cover

EAN: 6418074021946
EI. number:
 Finland 3421686
 Denmark 8212022661
 Italy 7352150

Including: Base with PUR gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

| Dimensions: | | | | Rating: | |
|-------------------------------|--------------------------|-----|-----|---|--|
| | L | W | H | | |
| mm: | 255 | 180 | 125 | Ingress Protection (EN 60529): IP 66/67 | |
| inch: | 10 | 7.1 | 4.9 | Impact Resistance (EN 50102): IK 08 | |
| Materials: | | | | Electrical insulation: Totally insulated | |
| Material: | PC | | | Halogen free (DIN/VDE 0472, Part 815): Yes | |
| Base colour: | RAL 7035 | | | UV resistance: UL 508 | |
| Cover colour: | Smoked grey | | | Flammability Rating (UL 746 C 5): UL 94 5V | |
| Cover screws material: | Polyamide | | | Glow Wire Test (IEC 695-2-1) °C: 960 | |
| Cover screws colour: | Black | | | NEMA Class: NEMA 1, 4, 4X, 6, 12, 13 | |
| Gasket material: | Polyurethane | | | Certificates: | |
| Temperatures: | | | | Germanischer Lloyd (GL) | |
| Short term: | -40 ... 120 °C | | | Underwriters Laboratories | |
| Continuous: | -40 ... 80 °C | | | Det Norske Veritas | |
| Short term: | -40 ... 250 °F | | | Fimko | |
| Continuous: | -40 ... 175 °F | | | Europe EN 50298 1998 | |
| Accessories: | | | | UL Canada | |
| MIV 200 | Mounting plate | | | Gost R | |
| MIN 15 | DIN-15 Mounting rail | | | | |
| MIN 20 | DIN-15 Mounting rail | | | | |
| MIV 15 | DIN-35 Mounting rail | | | | |
| MIV 20 | DIN-35 Mounting rail | | | | |
| FP A 200/180 | Front plate | | | | |
| HFP 180 | Front plate hinge series | | | | |

