



Sample photo

**Order symbol:** PC 3819 13 T  
**Product nbr:** 5330061  
**Description:** Enclosure, PC  
**Remarks:** Transparent cover

**EAN:** 6418074005472  
**EI. number:**  
 Finland 3423809  
 Italy 7402030D  
 Sweden 2539444

**Including:** Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

Dimensions:		L	W	H	Rating:
mm:		378	188	130	<b>Ingress Protection (EN 60529):</b> IP 66/67
inch:		14.9	7.4	5.1	<b>Impact Resistance (EN 50102):</b> IK 08/09
Materials:					
<b>Material:</b>		PC			
<b>Base colour:</b>		RAL 7035			
<b>Cover colour:</b>		Clear transparent			
<b>Cover screws material:</b>		Polyamide			
<b>Cover screws colour:</b>		Grey			
<b>Gasket material:</b>		Polyurethane			
Temperatures:					
<b>Short term:</b>		-40 ... 120 °C			
<b>Continuous:</b>		-40 ... 80 °C			
<b>Short term:</b>		-40 ... 250 °F			
<b>Continuous:</b>		-40 ... 175 °F			
Accessories:					
EKMVT		Mounting plate			
EKV 12		DIN-35 Mounting rail			
EKV 32		DIN-35 Mounting rail			
EKMZR		Extension frame			
Electrical insulation:		Totally insulated			
Halogen free (DIN/VDE 0472, Part 815):		Yes			
UV resistance:		UL 508			
Flammability Rating (UL 746 C 5):		UL 94 5V			
Glow Wire Test (IEC 695-2-1) °C:		960			
NEMA Class:		NEMA 1, 3, 3S, 4, 4X, 6, 6P, 12			
Certificates:					
		Underwriters Laboratories			
		Canadian Standards Association			
		Fimko			
		Europe EN 50298 1998			
		UL Canada			
		Gost R			

