



Sample photo

Order symbol: PCM 200/175 XG
Product nbr: 6015329
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074038371
EI. number:
 Finland 3421624
 Denmark 8212027404
 Sweden 2535363

Including: Base with metric knock-outs and PUR gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:			L	W	H	Rating:
mm:	255	180	175			Ingress Protection (EN 60529): IP 66/67
inch:	10	7.1	6.9			Impact Resistance (EN 50102): IK 08
Materials:						Electrical insulation: Totally insulated
Material:	PC					Halogen free (DIN/VDE 0472, Part 815): Yes
Base colour:	RAL 7035					UV resistance: UL 508
Cover colour:	RAL 7035					Flammability Rating (UL 746 C 5): UL 94 5V
Cover screws material:	Polyamide					Glow Wire Test (IEC 695-2-1) °C: 960
Cover screws colour:	Grey					NEMA Class: NEMA 1, 4, 4X, 6, 12, 13
Gasket material:	Polyurethane					Certificates:
Temperatures:						Germanischer Lloyd (GL)
Short term:	-40 ... 120 °C					Underwriters Laboratories
Continuous:	-40 ... 80 °C					Det Norske Veritas
Short term:	-40 ... 250 °F					Fimko
Continuous:	-40 ... 175 °F					Europe EN 50298 1998
Accessories:						UL Canada
MIV 200	Mounting plate					Gost R
MIN 15	DIN-15 Mounting rail					
MIN 20	DIN-15 Mounting rail					
MIV 15	DIN-35 Mounting rail					
MIV 20	DIN-35 Mounting rail					
FP A 200/180	Front plate					
HFP 180	Front plate hinge series					

